

Manufacturer	Equipment		Standard ⁽²⁾	Combination with SMD ⁽³⁾	Notification
	Designation	Configuration ⁽¹⁾			
CEIA S.p.A	02PN10K-EVO	<i>Hardware:</i> 02PN10K/PZ-EVO V2.00x <i>Control Unit Board</i> SCD73 <i>Antenna:</i> SS65 <i>Detection Algorithm:</i> PV 1010, IS=EU-STD-2 <i>CONOPS:</i> FI060K0098v1103xUK (Quick guide)	2	YES	12/03/2019
CEIA S.p.A	HI-PE PLUS	<i>Hardware:</i> HIPEPLUS/PZ <i>Antenna:</i> SS65 <i>Detection Algorithm:</i> LXDA2000 <i>CONOPS:</i> FI060K0108v2300	2	YES	08/07/2019
CEIA S.p.A	PMD3 Plus	<i>Hardware:</i> PMD3Plus/PZ <i>Antenna:</i> SS65 <i>Detection Algorithm:</i> LXDA2000 (EU-STD-2) <i>CONOPS:</i> FI060K0108v2310	2	YES	04/12/2020
CEIA S.p.A	02PN20	<i>Hardware:</i> 02PN20/PZ <i>Antenna:</i> SS65 <i>Detection Algorithm:</i> LXDA2000 (EU-STD-2) <i>CONOPS:</i> FI060K0108v2320	2	YES	19/03/2021

Manufacturer	Equipment		Standard ⁽²⁾	Combination with SMD ⁽³⁾	Notification
	Designation	Configuration ⁽¹⁾			
Garret	PD 6500i	<i>Hardware:</i> 2340510 and 2340720 <i>Antenna:</i> 223320x and 223335x <i>Detection Algorithm:</i> ECAC / SE=162 <i>CONOPS:</i> 1532010	2	NO	17/12/2021

Manufacturer	Equipment		Standard ⁽²⁾	Combination with SMD ⁽³⁾	Notification
	Designation	Configuration ⁽¹⁾			
Rapiscan	Metor 6E	<i>Hardware:</i> Electronics, p/n 23106448 <i>Antenna:</i> Coil Set1, p/n 23109437 Coil Set2, p/n 23109438 <i>Detection Algorithm:</i> Software, Detection Core, Metor 6E p/n 101021459, v1.00, EU2 <i>CONOPS:</i> CONOPS, ECAC CEP, Metor 6E, "Quick Guide", p/n D01499, v1	2	NO	08/07/2019
Rapiscan	Metor 900M	<i>Hardware:</i> Electronics, p/n 23113530 <i>Antenna:</i> RX Coils, p/n 101017805 TX Coils, p/n 101017806 <i>Detection Algorithm:</i> V 1.3.1 EU2 HD, Sensitivity 100 <i>CONOPS:</i> V1.0, p/n D05693	2	YES	17/12/2021

Manufacturer	Equipment		Standard ⁽²⁾	Combination with SMD ⁽³⁾	Notification
	Designation	Configuration ⁽¹⁾			
Nuctech	MD2000	<i>Hardware:</i> 1.0 <i>Antenna:</i> MBP1-2.13 MBP2-2.13 <i>Detection Algorithm:</i> 08.00.06.00 <i>CONOPS:</i> V1.0 / 01-2020	2	NO	07/04/2020

Note: ⁽¹⁾ Information on configuration is provided by the equipment manufacturer as part of the testing process.

Note: ⁽²⁾ Note that within the Standard no requirement for a maximum Non-Threat Alarm Rate exists.

Note: ⁽³⁾ Compliant to be used in combination with SMD, have passed the location indication test